

SECTION I – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **Clear Coat™**
PRODUCT DESCRIPTION: Acrylic Coating
Manufacturer: GLOBAL Encasement, Inc.
701 E. Santa Clara St., Ste 12, Ventura, CA 93001-5972
Contact #s: Tel. # (800) 266-3982 / Fax (800) 520-3291
Emergency Contact #s: (CHEMTREC) Tel.# (800) 424-9300
Website Address: www.encasement.com

SECTION II – COMPONENT INFORMATION

Material or Component:	CAS No.:
Water	7732-18-5
Tris(2-butoxyethyl)phosphate	78-51-3
Dibutyl Phalate	84-74-2
Diethylene glycol monobutyl ether	112-34-5

OSHA PEL or ACGIH TLV: This product contains no hazardous ingredients as per OSHA 29 CFR 1910.1200

SECTION III – HAZARD IDENTIFICATION

HMIS HAZARD RATING: Health: 1 Flammability: 0 Reactivity: 0 HAZARD INDEX: 0= Minimal, 1= Slight, 2= Moderate, 3= Serious, 4= Severe
--

EFFECTS OF OVER EXPOSURE:

Inhalation - Vapor or mist can cause irritation of the nose, throat and lungs.
Eye Exposure - Possibly slightly irritating to eyes with direct contact.
Skin exposure - Possible skin irritant with repeated or prolonged contact.

SECTION IV – FIRST AID INFORMATION**EMERGENCY FIRST AID PROCEDURES:**

Inhalation: Move subject to fresh air.
Eye & Skin contact: Flush eyes with large amounts of water for at least 15 minutes.
See a physician if irritation persists. Wash affected skin areas with soap and water.
Ingestion: If swallowed give 2 glasses of water to drink. See a physician.

SECTION V – FIRE AND EXPLOSION INFORMATION

FLAMMABILITY CLASSIFICATION: DOT - Not Regulated
Flash Point - Non Combustible
LEL - N/A
EXTINGUISHING MEDIA: N/A

UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212 F polymer film can burn.
SPECIAL FIRE FIGHTING PROCEDURES: For fires involving this material, do not enter any enclosed or confined space without proper protective gear, including self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency caused by a fire.

SECTION VI – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep spectators away. Floor may be slippery, use care to avoid falling. Scoop or shovel solid material into a suitable container for recovery or disposal. Keep spills and cleaning runoff out of municipal sewers or open bodies of water.

SECTION VII – HANDLING AND STORAGE INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING: Do not take internally. Follow standard guidelines concerning latex paint spraying activities.

PRECAUTIONS TO BE TAKEN IN STORING: KEEP MATERIAL FROM FREEZING, PRODUCT MAY COAGULATE. Keep tightly covered. Material may develop bacterial odor on long-term storage if contaminated.

KEEP AWAY FROM CHILDREN.

SECTION VIII – EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear suitable respirator (MSHA/NIOSH approved or equivalent) where exposure limits are exceeded.

VENTILATION: Mechanical local exhaust ventilation at point of containment release.

PROTECTIVE GLOVES: Impervious gloves for prolonged or repeated contact.

EYE PROTECTION: Chemical splash goggles (ANSI 2-87.1) or approved equivalent.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Liquid	Odor:	Mild scent
Color:	Milky White	VOC, grams/liter:	100
Flash Point:	N/A	pH:	9-10
Specific Gravity (water = 1.0):	1.0-1.2	Viscosity:	Water Like

SECTION X – STABILITY AND REACTIVITY INFORMATION

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

HAZARDOUS DECOMPOSITION PRODUCTS: Will not occur

CONDITIONS TO AVOID: Keep from freezing

INCOMPATIBILITY: None reasonably foreseeable

SECTION XI – TOXICOLOGICAL INFORMATION (will only print available data)

Carcinogenicity?: NO

Refer to section VII for proper handling.

No other toxicological information available.

