

Your Last Coat™



Environmentally
Advanced Solutions

1. PRODUCT NAME

YOUR LAST COAT™

2. MANUFACTURER

GLOBAL Encasement, Inc.
701 E. Santa Clara St., Ste 12
VENTURA, CA 93001-5972 USA
PHONE: (800) 266-3982
FAX: (800) 520-3291
Www.encasement.com

3. PRODUCT DESCRIPTION

YOUR LAST COAT™ is a high performance, water-based, acrylic, non-toxic, low VOC (4 g/l) coating that is tough, abuse-, rust-, mildew-, fire- and chemical-resistant and forms a waterproofing membrane. Its moisture vapor transmission qualities make it perfect for historic preservation and can be custom tinted almost any color. It can be applied over PrepLESS Primer™ to form a GLOBAL Encasement System.

YOUR LAST COAT™ is excellent for interior or exterior use over most surfaces: walls, ceilings, trim, ducts, pipes, roofing and siding, window sills, frames, trim, porch railings, posts, overhangs and fences. It securely seals and encases materials on wood, plaster, stucco, masonry, concrete, structural steel, Transite, Galbestos, shingles, built-up roofing, fiberglass vermiculite and ceramic fiber.

YOUR LAST COAT™ Features:

- Class A Fire Rated
- Extremely tough, durable and flexible
- Mildew and mold resistant
- Can be custom tinted almost any color
- Waterproof
- Flexible
- Low in V.O.C. (Volatile Organic Content)

4. TECHNICAL DATA AND PROPERTIES

Solids by weight:	67.4% (+/- 2%)
Solids by volume:	54% (+/- 2%)
Weight per gallon:	11.85 lbs
VOC:	4 g/l
Liquid appearance:	Bright White with mild scent
Viscosity:	105-120 KU
Drying time:	To Touch: 1-4 Hours Recoat After Dry To Touch: 2-8 Hrs Full Cure: 10-14 Days

YOUR LAST COAT™ has an elongation of 300% and a tensile strength of 200 psi (ASTM D412), superior flexibility (ASTM D522,A), high impact resistance (ASTM D2794), and adhesion (ASTM E736). This material has passed ASTM E-1795, the Standard for Liquid Coating Encapsulation Products for Leaded Paint in Buildings. This material has passed ASTM E-108 (comparable to U.B.C. S'd 32-7 and UL 790) is UL Listed and meets the requirements for Class A. This material has passed ASTM E-119 testing over fireproofing insulation, ASTM E-84, E-162, and QUV G53.

Your Last Coat™ is non-toxic, non-mercuric, and low in Volatile Organic Content (V.O.C.).

D.L. Laboratories Toxicological Report states: "There is no toxicological basis for limiting occupancy of a dwelling unit, or restricting entry of any resident including pregnant women and children under six years of age, to dwelling units during the application of your encapsulant."

5. PRODUCT INSTALLATION

- **YOUR LAST COAT™** is ready to use and should not be diluted.
- Apply by brush or roller, or airless sprayer.
- All surfaces must be clean, dry, and free of dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- Apply in temperatures between 50°F and 100°F.
- Dries in 2-8 hours. Cool temperatures and high humidity can affect dry and cure time.
- Follow manufacturer's application guidelines.
- Easy to use and clean up is with water.

COVERAGE:

YOUR LAST COAT™ coverage rate on a flat surface is:

Dry Mills = 6 @ 160 sq. ft./gallon
= 8 @ 120 sq. ft./gallon
= 10 @ 96 sq. ft./gallon
= 12 @ 80 sq. ft./gallon
= 14 @ 68 sq. ft./gallon

Coverage varies depending upon the porosity and texture of the surface being encased.

Spray Application: Use self-cleaning reversible spray tip
Size .019-.035 (.021 is most often used).

Brush: Use any nylon bristle brushes.

Roller: Use a ¾ inch nap.

6. AVAILABILITY AND COST

Call GLOBAL Encasement, Inc. at 800-266-3982 for pricing and availability.

7. WARRANTY

GLOBAL Encasement, Inc. can warrant for a period of up to twenty (20) years from the date of purchase that **YOUR LAST COAT™** is free of any defects in manufacturing. The Limited Warranty herein described shall be in lieu of any other warranty, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

GLOBAL Encasement's sole liability under this Limited Warranty shall be, at its option, to replace any portion of the product proven to be defective in manufacture.

Any defects discovered must be reported to GLOBAL Encasement, Inc. within the Limited Warranty period, and no later than 30 days after discovery.

This Limited Warranty does not extend to liability for any damages due to abuse by occupants, improper maintenance, water damage, or any other causes beyond anticipated conditions and the manufacturer's control.



GLOBAL Encasement, Inc.
www.encasement.com

World-Class Solutions for Better Building Environments

