

Your Last Coat™



Environmentally
Advanced Solutions

1. PRODUCT NAME

Your Last Coat™

2. MANUFACTURER

GLOBAL Encasement, Inc.
701 E. Santa Clara St., Ventura, CA 93001 USA
Phone: (800) 266-3982 / Fax: (800) 520-3291
www.encasement.com

3. PRODUCT DESCRIPTION

Your Last Coat™ is a high performance, UV resistant, water-based, acrylic, non-toxic, zero VOC green coating that is tough, abuse-, rust-, rot-, mildew-, fire- and chemical-resistant and forms a waterproofing membrane. Its moisture vapor transmission qualities make it perfect for historic preservation and can be custom tinted almost any color.

USES: Over most interior or exterior surfaces - wood, plaster, stucco, masonry, concrete, metal, structural steel, transite, galbestos, wood or asphalt roofing shingles, built-up roofing, fiberglass, vermiculite and ceramic fiber.

Use it to seal and encase roofing, Asbestos-Containing Materials (ACM), Lead-Based Paint (LBP), walls, ceilings, trim, ducts, pipes, siding, window trim, porch railings, posts, overhangs, fences, and transite.

Your Last Coat™ GREEN Features:

- Class A Fire Rated
- UL Listed Roof Coating
- Certified Lead Encapsulant - ASTM E-1795 Tested
- Approved for use over Asbestos-Containing Materials
- LEED Solar Reflective Energy Star Roof Coating
- LEED Zero VOC, Non-Toxic
- Mercury and Lead Free
- Sustainable/Renewable
- Easy to use, cleans up with water

Your Last Coat™ PERFORMANCE Features:

- Extremely tough, durable and flexible
- Mildew and mold-resistant
- Fire-, chemical-, impact-, and abuse-resistant
- Waterproof, breathable
- Can be custom tinted almost any color

4. TECHNICAL DATA AND PROPERTIES

Solids by weight: 66% (+/- 2%)
Solids by volume: 52% (+/- 2%)
Weight per gallon: 11.85 lbs
VOC: Zero
Liquid appearance: Bright white with mild scent
Viscosity: 110 +/-10 KU
Drying time: To Touch: 1-4 hours
Recoat After Dry To Touch: 2-8 hours
Full Cure: 10-14 days

Your Last Coat™ has an elongation of 329% and a tensile strength of 304 psi, superior flexibility, high impact resistance and adhesion all tested in accordance with (ASTM D 6083) standard testing protocol for liquid applied roofing systems.

Why Replace? – Just Encase!



GLOBAL Encasement, Inc.

World-Class Coatings for Better Building Environments

5. PRODUCT INSTALLATION

- **Your Last Coat™** is ready to use.
- DO NOT DILUTE. PROTECT FROM FREEZING.
- Apply by brush or roller, or airless sprayer.
- All surfaces must be clean, dry, and free of mold, mildew, chalking, dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- Best applied in temperatures between 50°F and 100°F.
- Dries in 2-8 hours. Cool temperatures and high humidity can affect dry and cure time.
- Follow manufacturer's application guidelines.
- Easy to use and clean up is with water.

COVERAGE:

Your Last Coat™ Coverage rate varies depending upon the porosity and texture of the surface being encased.

Theoretical coverage on a flat non-porous surface is:

Interior System = 7 mil DFT @ 137 sq. ft./gallon
Exterior System = 14 mil DFT @ 68 sq. ft./gallon

On Roofing:

10-Year System = 16 mil DFT @ 60 sq. ft./gallon
20-Year System = 32 mil DFT @ 30 sq. ft./gallon

*DFT: Dry Film Thickness

Product	Wet Mils	Dry Mils
	14	7
Your Last Coat™	27	14
	31	16
	62	32

Follow manufacturer's application guidelines.

Spray Application: Use self-cleaning reversible spray tip size .019-.035 (.021 is most often used).

Brush: Use any nylon bristle brushes.

Roller: Use a ¾ inch nap.

6. AVAILABILITY AND COST

Call GLOBAL Encasement, Inc. at 800-266-3982 for pricing and availability.

7. WARRANTY

GLOBAL Encasement, Inc. can warrant for a period of up to twenty (20) years from the date of purchase that **Your Last Coat™** is free of any defects in manufacturing. The Limited Warranty herein described shall be in lieu of any other warranty, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

GLOBAL Encasement, Inc.'s sole liability under this Limited Warranty shall be, at its option, to replace any portion of the product proven to be defective in manufacture.

Any defects discovered must be reported to GLOBAL Encasement, Inc. within the Limited Warranty period, and no later than 30 days after discovery.

This Limited Warranty does not extend to liability for any damages due to abuse by occupants, improper maintenance, water damage, or any other causes beyond anticipated conditions and the manufacturer's control.



Updated: July 2015



GSA Worldwide Service
Contract #GSO6F0010J

