

Prep-LESS Primer™



1. PRODUCT NAME

The Original PrepLESS Primer™

2. MANUFACTURER

GLOBAL Encasement, Inc.
701 E. Santa Clara St.
Ventura, CA 93001 USA
Phone: (800) 266-3982
Fax: (800) 520-3291
www.encasement.com

3. PRODUCT DESCRIPTION

PrepLESS Primer™ is a clear water-based, non-toxic, flexible, zero VOC, super compliant architectural green coating primer-sealer-neutralizer that acts as a stabilizer for building surfaces that can be only marginally cleaned and where tenacious adhesion is needed. It applies milky white and dries clear, leaving a tacky finish ready to receive any of GLOBAL Encasement, Inc.'s topcoats, including **LeadLock™**, **AsbestoSafe®**, **Your Last Coat™**, **RoofCoat™**.

PrepLESS Primer™ Features:

- Class A Fire Rated
- Less Prep. Less Mess
- Zero Volatile Organic Content (VOC)
- Excellent for interior or exterior use
- Easy to use
- Waterproof
- Flexible
- Re-attaches loose, peeling, flaking paint

PrepLESS Primer™ can be applied over Lead-Based Paint (LBP), Asbestos Containing Materials (ACM), and surfaces that are difficult to adhere to, such as cracked and painted plaster, concrete, masonry, stucco, fiberglass, vermiculite, ceramic fiber. It is excellent for interior and exterior walls, ceilings, trim, wallboard, sheet rock, ducts, pipes, roofing, all non-friction surfaces, treated or untreated wood, stone and metal.

It is also excellent for making surface repairs. To bridge large cracks or patch holes, use **PrepLESS Primer™** with **Globe Caulk™** or **GEI Fabric** reinforcement.

4. TECHNICAL DATA

Solids by volume: 48.4% (+/- 2%)
Weight per gallon: 8.67 lbs
VOC: Zero
Liquid appearance: Milky white
Drying time: To Touch: 1-4 Hours
Recoat After Dry To Touch: 2-8 Hours
Full Cure: 10-14 Days
Clean up: Warm, soapy water

PrepLESS Primer™ has an elongation of 4000% at 70°F; superior low temperature flexibility; 9,995 lbs/sf of adhesion strength; has passed ASTM E-84, E-162, ASTM E-119 testing over fireproofing insulation.

This zero VOC product more than conforms to the minimum VOC requirements set forth by the SCAQMD (Southern California Air Quality Management District) and is considered a super compliant architectural zero VOC green coating.

5. PRODUCT INSTALLATION

- **PrepLESS Primer™** is ready to use.
- PROTECT FROM FREEZING.
- Apply by brush or roller, or airless sprayer.
- All surfaces must be clean, dry, and free of mold, mildew, chalking, dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- Apply in temperatures between 50°F and 100°F.
- Cool temperatures and high humidity can affect dry and cure time.
- Follow manufacturer's application guidelines.
- Easy to use and clean up is with water.

COVERAGE:

PrepLESS Primer™ may be brushed, rolled or spray applied.

The coverage varies depending on porosity, mil thickness, and texture of the surface being encased.

Calculated coverage rates on a flat surface are as follows:

- = 6 mil DFT @ 120 sq. ft./gallon
- = 7 mil DFT @ 102 sq. ft./gallon
- = 8 mil DFT @ 90 sq. ft./gallon
- = 9 mil DFT @ 80 sq. ft./gallon
- = 10 mil DFT @ 72 sq. ft./gallon
- = 11 mil DFT @ 65 sq. ft./gallon
- = 12 mil DFT @ 60 sq. ft./gallon

Spray Application: Use self-cleaning reversible spray tip size .017-.025 (.019 is most often used).

Brush: Use any nylon bristle brushes.

Roller: Use a ¾ inch nap.

6. AVAILABILITY AND COST

Call GLOBAL Encasement, Inc. at 800-266-3982 for pricing and availability.

Available Package Sizes: 5 gallon pail, 55 gallon drum & 275 gallon tote.

7. WARRANTY

GLOBAL Encasement, Inc. can warrant for a period of up to twenty (20) years from the date of purchase that **PrepLESS Primer™** is free of any defects in manufacturing. The Limited Warranty herein described shall be in lieu of any other warranty, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

GLOBAL Encasement, Inc.'s sole liability under this Limited Warranty shall be, at its option, to replace any portion of the product proven to be defective in manufacture.

Any defects discovered must be reported to GLOBAL Encasement, Inc. within the Limited Warranty period, and no later than 30 days after discovery.

This Limited Warranty does not extend to liability for any damages due to abuse by occupants, improper maintenance, water damage, or any other causes beyond anticipated conditions and the manufacturer's control.



Why Replace? – Just Encase!

GLOBAL Encasement, Inc.

World-Class Solutions for Better Building Environments

Updated: Jan 2019

